

Para Shotblast Rubber

Unbeatable tensile strength, natural tan rubber

- Excellent resistance to wear and abrasion.
- Widely used as protective screening for shotblasting.
- Also used in strip or gasket form where durability is essential.
- 45 degrees shore A hardness.
- Tensile strength at break: 15 Mpa.
- Elongation at break: 400%.



Parts

Part Number	Size	Colour	Weight (kg)
PRS00001C	1.4 m x per linear metre (3 mm)	Tan	4.7
PRS00002C	1.4 m x per linear metre (6 mm)	Tan	8.5
PRS00004	1.4 m x 5.0 m (12 mm)	Tan	98
PRS00003	1.4 m x 5.0 m (10 mm)	Tan	84
PRS00002	1.4 m x 10 m (6 mm)	Tan	85
PRS00001	1.4 m x 10 m (3 mm)	Tan	47

Technical Specifications

Material	Natural rubber
Surface Finish	Smooth
Product Height	3 mm - 12 mm
Roll Length	5 m, 10 m
Min. Operating Temperature	-40°C
Max. Operating Temperature	+80°C
Typical Applications	Shotblasting screens
Other Product Performance Information	Test Temperature 25°C Relative Humidity 35% Correlation criterion GB/T528-1998 GB/T3512-1989 GB/T531-1992