

COBAGRiP® Stair Tread

Increase stair safety with a non-slip silicon carbide surface finish

- Fully cover a stair area with an anti-slip surface.
- Each stair tread covers the entire step area, overlapping the edge onto the riser acting as stair protectors.
- Available in yellow or white, which both meet current Equality Act requirements.
- The perfect match with our COBAGRiP Sheet.











Styles Available



White



Yellow

Parts

Part Number	Size	Colour	Weight (kg)
GRP010705S	0.75 m x 345 mm x 55 mm	Black/Yellow	2.55
GRP010135S	0.75 m x 345 mm x 55 mm	Black/White	2.55
GRP010702S	2.0 m x 345 mm x 55 mm	Black/Yellow	6.8
GRP010701S	3.0 m x 345 mm x 55 mm	Black/Yellow	10.2
GRP010134S	1.0 m x 345 mm x 55 mm	Black/White	3.4
GRP010133S	1.5 m x 345 mm x 55 mm	Black/White	5.1
GRP010132S	2.0 m x 345 mm x 55 mm	Black/White	6.8
GRP010131S	3.0 m x 345 mm x 55 mm	Black/White	10.2
GRP010704S	1.0 m x 345 mm x 55 mm	Black/Yellow	3.4
GRP010703S	1.5 m x 345 mm x 55 mm	Black/Yellow	5.1

Technical Specifications

Material	GRP with quartz grit bonded on top (with resin)
Surface Finish	Quartz grit
Product Height	55 mm
Min. Operating Temperature	-50°C
Max. Operating Temperature	+90°C
Environmental Resistance	Suitable for indoor and outdoor environments
Typical Applications	External steps
Installation Method	Bond or screw to surface
Cleaning Method	COBAGRiP should be almost maintenance free in most outside environments. Natural elements will have the effect of cleaning COBAGRiP. Brushing and flushing with a mild detergent solution may be desirable now and again to restore appearance.
Fire Tested to	DIN 13501: Bfl - s1 (2018) & EN ISO 11925-2:2020 & EN ISO 9239-1:2010 (both 2021)
Slip Tested to	DIN 51130 - R13 & BS 7976-2 - low slip potential
Product Thickness:	5 mm

Additional Information

Installation Guide

COBAGRiP EN ISO11925 2 2020 Reaction to Fire

COBAGRiP EN ISO9239 1 2010 Reaction to Fire

COBAGRiP Fire Test EN13501 1 2018

COBAGRiP Pendulum Slip Test BS 7676

COBAGRiP Ramp Slip Test DIN 51130