

Fatigue Lock®

Premium mid-size interlocking anti-fatigue tile



- This extra thick tile provides comfort and fatigue relief for standing workers.
- Precision designed tiles seamlessly clip together for smooth raised floor surface.
- Convenient tile size allows for easy planning.
- Can be used to cover large or unusually shaped workstations.
- Made from rubber for durability, slip, and impact resistance.
- Tile option with holes is ideal for wet workplaces in need of drainage.
  .
- Solid and holed version can be used together in one installation.
- Ramped edges prevent trips and are available in black or yellow.
- Easily cleaned with a jet washer or hose.
- Slip tested to DIN 51130.















Parts

Part Number	Size	Colour	Weight (kg)
FLS010001	0.5 m x 0.5 m	Black	3.2

Technical Specifications

Material	Rubber, including 25% NBR and 50% recycled content
Recycled Material Content %	65%
Surface Finish	Textured solid, or textured with holes
Product Height	24 mm
Min. Operating Temperature	-20°C
Max. Operating Temperature	+140°C
Environmental Resistance	Suitable for wet and dry environments
Typical Applications	General industrial
Slip Tested to	DIN 51130 - R10

Additional Information

Installation Guide

Fatigue Lock DIN 51130 Ramp Slip Test

Fatigue Lock Solid DIN 51130 Ramp Slip Test