





Shotblast Rubber

Cost-effective, abrasion-resistant rubber sheeting

- Smooth surfaced, economical sheeting with high tensile strength.
- Ideal for shot-blast cabinet lining, chute lining, skirting rubber, seals and scrapers.
- 62 degrees shore A hardness.
- Tensile strength at break: 10.0 Mpa.
- Elongation at break: 350%.

Parts

Part Number	Size	Colour	Weight (kg)
SRS00001C	1.4 m x per linear metre (3 mm)	Black	6.1
SRS00002C	1.4 m x per linear metre (4.5 mm)	Black	11.2
SRS00003C	1.4 m x per linear metre (6 mm)	Black	10.4
SRS00004	1.4 m x 5.0 m (12 mm)	Black	105
SRS00003	1.4 m x 10 m (6 mm)	Black	105
SRS00002	1.4 m x 10 m (4.5 mm)	Black	79
SRS00001	1.4 m x 10 m (3 mm)	Black	53

Technical Specifications

Material	Natural rubber and SBR
Surface Finish	Smooth
Product Height	3 mm - 12 mm
Roll Length	5 m, 10 m
Min. Operating Temperature	-30°C
Max. Operating Temperature	+80°C
Other Product Performance Information	Test Temperature 25°C Relative Humidity 35% Test by GB5574-94 Correlation criterion GB/T528-1998 GB/T3512-1989 GB/T531-1992