





Insertion Black Rubber

Features embedded textile reinforcement for increased tensile strength and tear resistance



- Suitable for use in air, hot water and hydraulic services.
- A popular gasket material for applications with high compression loads.

Parts

Part Number	Size	Colour	Weight (kg)
IRS00002C	1.4 m x per linear metre (3 mm)	Black	7.11
IRS00003C	1.4 m x per linear metre (4.5 mm)	Black	9.45
IRS00004C	1.4 m x per linear metre (6 mm)	Black	13.05
IRS00005C	1.4 m x per linear metre (10 mm)	Black	22.1
IRS00006C	1.4 m x per linear metre (12 mm)	Black	26.26
IRS00001C	1.4 m x per linear metre (1.8 mm)	Black	4.7
IRS00001	1.4 m x 10 m (1.8 mm)	Black	47
IRS00006	1.4 m x 5.0 m (12 mm)	Black	131.3
IRS00005	1.4 m x 5.0 m (10 mm)	Black	110.5
IRS00004	1.4 m x 10 m (6 mm)	Black	130.5
IRS00003	1.4 m x 10 m (4.5 mm)	Black	94.5
IRS00002	1.4 m x 10 m (3 mm)	Black	71.15

Technical Specifications

Material	SBR
Surface Finish	Smooth
Product Height	1.8 mm - 12 mm
Roll Length	5 m, 10 m
Min. Operating Temperature	-30°C
Max. Operating Temperature	+70°C
Other Product Performance Information	Test Temperature: 25°C Relative Humidity: 35% Correlation criterion: GB/T528-1998 GB/T3512-1989 GB/T531-1992
Tensile Strength	3.4 MPa
Elongation	190%
Specific Weight (g/cm^3)	1.6
Shore A Hardness	70 ±5