

Bubblemat Nitrile

Nitrile anti-fatigue mat designed for resistance to oil, chemicals and lubricants in demanding work environments

- High-quality anti-fatigue mat.
- Raised bubble patterned surface encourages movement and stimulates circulation, reliably preventing signs of fatigue.
- Increased work safety due to slip resistance.
- NBR rubber (nitrile) for good resistance to oil, lubricants and chemicals.
- Available as individual mats or interlocking sections for longer production lines.











Parts

Part Number	Size	Colour	Weight (kg)
BF010004N	0.6 m x 0.9 m	Black (Nitrile)	5.75
BF010003N	0.6 m x 0.9 m	Black (Nitrile)	5.75
BF010002N	0.9 m x 1.2 m	Black (Nitrile)	10
BF010001N	0.6 m x 0.9 m	Black (Nitrile)	6.25

Technical Specifications

Material	NBR
Recycled Material Content %	23% recycled content
Surface Finish	Bubble
Product Height	14 mm
Min. Operating Temperature	-20°C
Max. Operating Temperature	+50°C
Resistance to Chemicals	NBR offers excellent resistance to oils and chemicals
Environmental Resistance	Suitable for predominantly dry environments
UV Resistance	Yes
Typical Applications	General industrial
Installation Method	Loose lay interlocking mats
Cleaning Method	Use a high pressure hose (not exceeding 60psi) to remove the dirt and debris on the mats. For best results use a mild detergent (pH 4.0-9.0) to clean the mats. Do not use steam or degreasers or caustic chemicals. Do not mechanically scrub the mats
Tensile Strength	3 MPa
Elongation	250%
Application Temperature	-30°C to 50°C
Manufacturing process	Compression moulding