











COBATrack Tile

Instant access. Zero ground damage

- Impact-resistant polypropylene tiles for temporary ground protection and access routes.
- Slip-resistant surface improves grip for pedestrians and light vehicles.
- Independently tested to withstand loads of up to 4.41 tonnes (tested on a tray containing Type 1 MOT aggregate), providing additional confidence in performance under demanding site conditions.
- Engineered to withstand pressures of up to 272 kN/m without compromising performance.
- Suitable for grass, soil and uneven terrain.
- Interlocking system creates stable temporary flooring without specialist tools.
- 12 mm thick construction balances strength with manageable handling.
- Reusable design reduces reinstatement and repair costs.
- Specified for temporary pedestrian walkways, site access routes and event flooring over grass or soft ground.
- Suitable for construction sites, outdoor shows, school grounds and public events where protecting turf and maintaining safe footing is essential.
- Interlocking ramped edges are available to provide a smooth transition between matting and surrounding floor surfaces.

Parts

Part Number	Size	Colour	Weight (kg)
CT010001X16	450 mm x 150 mm	Black	4
CT010001	450 mm x 150 mm	Black	0.25

Technical Specifications

Material	PP
Surface Finish	Slip resistant raised pattern
Product Height	12 mm
Min. Operating Temperature	-10°C
Max. Operating Temperature	+50°C
Environmental Resistance	Suitable for outdoor use
Typical Applications	Construction, landscaping, events, catering and temporary car parks
Installation Method	Loose lay interlocking tiles
Load Achieved (Tonnes):	4.41
Pressure (kN/m):	272

Additional Information

Installation Guide

Test Certificate - Load test