

Tough Lock Anti-Fatigue Tile Edges

Improve compliance. Reduce trip hazards

- Hardwearing PVC ramp edges designed to create smooth, bevelled transitions.
- 15 mm thickness aligns with Tough Lock tile height for safe installation.
- Available in male, female and corner formats for full border systems.
- High-visibility yellow and orange options enhance workplace safety.
- Reduces edge trip hazards and improves compliance.
- Used to finish exposed edges around anti-fatigue work areas in production cells, warehouse pick faces and fabrication bays.
- Particularly important where foot traffic or pallet trucks transition between concrete floors and raised tile systems.

















Parts

Part Number	Size	Colour	Weight (kg)
TAC170001FX4	100 mm x 600 mm	Orange	1.48
TAC170001MX4	100 mm x 600 mm	Orange	1.48
TAE170001FX4	100 mm x 500 mm	Orange	1.24
TAE170001MX4	100 mm x 500 mm	Orange	1.36
TAC070001FX4	100 mm x 600 mm	Yellow	1.48
TAC070001MX4	100 mm x 600 mm	Yellow	1.48
Part Number	**Size**	**Colour**	**Weight (kg)**
TAE070001FX4	100 mm x 500 mm	Yellow	1.24
TAE070001MX4	100 mm x 500 mm	Yellow	1.36
TAC170001F	100 mm x 600 mm	Orange	0.37
TAC170001M	100 mm x 600 mm	Orange	0.37
TAE170001F	100 mm x 500 mm	Orange	0.31
TAE170001M	100 mm x 500 mm	Orange	0.34
TAC070001F	100 mm x 600 mm	Yellow	0.37
TAC070001M	100 mm x 600 mm	Yellow	0.37
TAE070001F	100 mm x 500 mm	Yellow	0.31
TAE070001M	100 mm x 500 mm	Yellow	0.34

Technical Specifications

Material	Hardwearing PVC
Product Height	15 mm
Min. Operating Temperature	-10°C
Max. Operating Temperature	+60°C
Environmental Resistance	Suitable for dry indoor environments
Typical Applications	Used with Tough Lock Anti Fatigue Tiles
Installation Method	Interlocking edges

Additional Information

Installation Guide