





EPDM Rubber

Excellent resistance to ozone, oxidants, water and harsh weather conditions



- High performing all rounder, ideal for marine and outdoor applications.
- Common uses include; seals, o-rings, glass-run channels, radiators, garden and appliance hose, tubing, pond liners, washers, belts and electrical insulation.
- 67 degrees shore A hardness.
- Tensile strength at break: 5.0 Mpa.
- Elongation at break: 300%.

Parts

Part Number	Size	Colour	Weight (kg)
EPDM00003C	1.4 m x per linear metre (4.5 mm)	Black	9.1
EPDM00004C	1.4 m x per linear metre (6 mm)	Black	12.3
EPDM00001C	1.4 m x per linear metre (1.5 mm)	Black	3.7
EPDM00002C	1.4 m x per linear metre (3 mm)	Black	6.33
EPDM00004	1.4 m x 10 m (6 mm)	Black	123
EPDM00003	1.4 m x 10 m (4.5 mm)	Black	91
EPDM00002	1.4 m x 10 m (3 mm)	Black	63.3
EPDM00001	1.4 m x 10 m (1.5 mm)	Black	37

Technical Specifications

Material	EPDM and SBR
Surface Finish	Smooth
Product Height	1.5 mm - 6 mm
Roll Length	5 m, 10 m
Min. Operating Temperature	-30°C
Max. Operating Temperature	+80°C
Other Product Performance Information	Test Temperature: 25°C Relative Humidity: 35% Correlation criterion: GB/T528-1998 GB/T3512-1989 GB/T531-1992