

COBAstat®

Comfortable anti-static mat for dry environments

- Comfortable and durable floor mat protects operatives from static build-up.
- ESD version of our popular Orthomat® anti-fatigue range.
- Grounded via a 10 mm male stud fitted to the mat.
- Maximum performance when used with grounding wire.
- Available as a handy COBAstat® Floor Kit with accessories provided.
- Tested to EN14041 resistance requirements.
- Resistance point to point (Rp-p): 2.0 x 10^{10} Ω.
- Resistance to groundable point (Rgp): 4.6 x 10^{10} Ω.
- Volume resistance (Rv): 1.1 x 10^{9} Ω.













Parts

Part Number	Size	Colour	Weight (kg)
AS060003C	0.9 m x per linear metre	Grey	2
AS060003	0.9 m x 18.3 m	Grey	40
AS060002	0.9 m x 1.5 m	Grey	4.5
AS060001	0.6 m x 0.9 m	Grey	2

Technical Specifications

Material	Closed cell PVC (Foam)
Surface Finish	Pebble
Product Height	9 mm
Min. Operating Temperature	0°C
Max. Operating Temperature	+60°C
Resistance to Chemicals	PVC is resistant to many different chemicals, alkalis and general industrial chemicals. PVC resists alcohols, aliphatic hydrocarbons, oils, weak acids, strong mineral acids and alkalis. PVC resists oil and grease if properly cleaned. PVC does not resist organic solvents, ketones, esters and aromatic hydrocarbons. Please contact us for more specific details
Environmental Resistance	Suitable for dry indoor environments
Typical Applications	Around machinery where static build up is common
Installation Method	Loose lay
Cleaning Method	Brush or mop the top surface
Volume resistance (Rv):	1.1×10^{9} Ω
Resistance to groundable point (Rgp):	4.6×10^{10} Ω
Resistance point to point (Rp-p):	2.0×10^{10} Ω

Additional Information

COBAstat ESD Test BS EN 14041